

Coming soon ...



werwie

Mit uns baut man Straßen
Paving your way

ID: TRBD405

Category: Tractor

Manufacturer: JOHN DEERE

Model: 7R 350

Year of manufacture: 2023

Operating hours: 736 h

Power: 350 PS

Description:

- John Deere Signature Edition
- John Deere PowerTechT 9.0L diesel engine, 6-cylinder, EPA exhaust emission standard FT4/EU Stage V
- AutoPowrT IVTT transmission, 50 km/h
- CommandPROT with linear transmission control via left-hand direction control lever
- Ultimate comfort package
- ActiveSeatT II
- Ultimate visibility package
- Without receiver
- CommandCenterT 4600 (4th Gen)
- Automation Activation 4.0 for Gen 4 CommandCenterT 4600
- Hardware only for JDLink - subscription not included
- Reactive steering
- Hydraulic pump, Throughput capacity 223 l/min
- Five premium remote auxiliary control units at the rear with electrohydraulic control, premium connection couplings and high-pressure relief levers
- PTO 35 mm, 540E/1000/1000E 1/min, PTO 45mm (1¾") 1000 1/min, electronically switchable in cab
- Three-point hitch (Cat. 3/3N) with 7,847 kg lifting capacity, with convertible catch hooks, quick couplers (Cat. 3) and deluxe stabilizer struts
- 3-in-1 mounting bracket, including rails and drawbar category 4, for 51 mm bolts, including clevis
- 1300 series front-wheel drive axle with TLST Plus, drive shaft protection, hydraulically actuated differential lock and oil-cooled front disc brakes
- Rear axle diameter 120 mm, length 2550 mm
- Rear wheels and tires VF750/70R44 183D R1W
- Front tires VF650/60R34 168D R1W
- Cast wheels with double-tapered hub
- Radar with dual-beam sensor
- Foot-operated speed control
- Immobilizer
- Right-mounted controls on rear fender
- Package loader and driving headlamps
- Integrated rotating beacon lights
- Heavy-duty alternator, 250 A
- Tractor Implement Management (TIM) - Activation for Tractor
- Additional hydraulic connections (Load Sensing) -¾"
- Front PTO with 35 mm, 6 teeth, 1000 1/min, direction of rotation clockwise in direction of travel (type 1)
- Automatic trailer hitch for 3-in-1 hitch system
- 80 mm ball head coupling for 3-in-1 mounting bracket
- Hydraulic top link rear - Cat. 3 (90 mm)
- Trailer brake, dual-line compressed air system
- Pivoting front fenders - width 620 mm
- Fender, rear additional cover - width 2.75 m
- Front hitch (Premium) with two hydraulic connections at the front
- Maximum permissible Weight 18 t



werwie GmbH

Rudolf-Diesel-Strasse 3, 54329 Konz, Germany

Phone: +49 6501 93630

Fax: +49 6501 9363-63

Email: werwie@werwie.com